




MACHINE MODEL	HE20	HE50	HE1C	HE3C	HE6C	HE1K	HE3K	HE5K	HE10K	HE16K	HE30K	HE65K
NOMINAL WEIGHT CAPACITY (Kg)	20	50	100	300	650	1000	3000	5000	10000	16000	30000	65000
OVER LOAD PERMITTED UP TO (Kg)	30	75	200	450	1000	1800	4000	7500	12500	20000	40000	75000
MAXIMUM DIAMETER OF ROTOR (mm)	500	700	900	1150	1350	1500	2100	2500	3000	3500	4000	4500
MAXIMUM LENGTH OF BED (mm)										Specially Executed Based on the Requirement		
BED SIZE - S	350	600	600	600	1200	2400	2400	2400	3600			
BED SIZE - M	650	900	1200	1600	2300	3600	3600	3600	7200			
BED SIZE - L	950	1200	1800	2300	3000	4800	4800	4800	10800			
MINIMUM DISTANCE BETWEEN PEDESTALS (mm)	30	40	50	50	55	55	80	100	200	250	250	300
JOURNAL DIAMETER RANGE (mm)	8-50	8-60	10-80	12-100	15-120	15-140	25-180	25-250	40-300	70-350	70-350	130-500
MINIMUM RESIDUAL UNBALANCE (mmg)	0.5	0.5	0.75	0.75	1.0	2.5	6.0	10.0	25.0	25.0	30.0	40.0

Machine Confirm to ISO 2953 Balances to ISO 1940 Requirements

Precibalance Dynamic Balancing Machines Pvt Ltd



B-52, Sipcot Industrial Estate, Irunkattukottai
 Sriperumpudur, India - 602105.
 Ph. No : +91 9789055141 / 142
 Fax No : +91
 Website : www.precibalance.com
 email : sales@precibalance.com